

**S-300i**

## AUDIOPHILE GRADE INTEGRATED AMPLIFIER

# KRELL

THE LEADER IN AUDIO ENGINEERING



Featuring iPod connectivity, the S-300i delivers award winning performance in a smart, elegant package.

# S-300i

AUDIOPHILE GRADE INTEGRATED AMPLIFIER

## DESIGN

### Power Supply

Employing a massive 750 VA toroidal transformer and 38,000 microfarads of capacitance, the S-300i sets the performance standard for integrated amplifiers.

### Power output

At 150 Watts per channel into 8 Ohms and 300 Watts per channel into 4 Ohms the S-300i is built to meet the demands of today's latest loudspeaker technology.

### Circuitry

A KRELL Class A, direct coupled design, fully balanced preamplifier circuitry utilizing KRELL Current Mode topologies provides unequaled signal bandwidth. Direct coupled circuitry eliminates impact-robbing capacitors from the signal path ensuring the preservation of the audio signal.

Unique for the category, the S-300i taps audio from the fully differential output included in the internal DACs of an iPod/ iPhone and maintains this balanced signal throughout the circuitry. A direct iPod connectivity cable is provided.

The S-300i has balanced, single-ended, and iPod inputs. KRELL Theater Throughput mode is assignable to an input, allowing simple integration into a home theater system.

### Convenience

A new menu system, adjustable via the custom machined volume control or remote control, allows personalization of input labels, volume gain and balance settings as well as several other functions.

The included solid aluminum remote control replicates all front panel options as well as providing control for a connected iPod/ iPhone. The S-300i also has 12volt trigger input/ output, RS-232 and RC5 capabilities.

WBT binding posts are incorporated, providing superior loudspeaker cable terminations. The S-300i is also rack mountable with included rack ears

Available in brushed aluminum silver finish only

## FEATURES

- Stereo Integrated Amplifier
- 150 W, 300 W (8, 4 Ohms)
- 750 VA toroidal transformer
- 38,000 microfarads of capacitance
- Krell Current Mode™
- RS-232, RC-5, 12 VDC Triggers
- Discrete Balanced Class A Input Stages
- Direct iPod Connection with Balanced Circuitry
- 17.25 W, 4.00 H, 17.50 D in.  
43.82 W, 10.16 H, 44.45 D cm



Krell Industries LLC • 45 Connair Road • Orange, CT 06497-3697 USA  
Tel: 203-799-9954 • Fax: 203-799-9796 • Sales Fax: 203-891-2028 • [contact@krellonline.com](mailto:contact@krellonline.com) • [www.krellonline.com](http://www.krellonline.com)

All operational features, functions, specifications, and policies are subject to change without notice.

Krell® is a registered trademark of Krell Industries LLC, and is restricted for use by Krell Industries LLC, its subsidiaries, and authorized agents. Theater Throughput™ and Krell Current Mode™ are trademarks of Krell Industries LLC. All other trademarks and trade names are registered to their respective companies. © 2009 by Krell Industries LLC. All rights reserved.